



ROLED

IP67-KLASSAD

Ø 70MM

TEKNISK INFORMATION

G - Borsilikatglas

PMMA - Polykarbonat

ART. NR.	TYP	GLAS	SPÄNNING	EFFEKT	LÄNGD
591-159-002	RoLED 70/408	G	24 VDC	14 W	448 mm
591-163-001	RoLED 70/216	PMMA	230 VAC	14 W	448 mm
591-163-002	RoLED 70/216	G	230 VAC	14 W	448 mm
591-155-002	RoLED 70/416	G	24 VDC	28 W	758 mm
591-155-003	RoLED 70/416	G	24 VDC	28 W	725 mm
591-155-004	RoLED 70/41B	PMMA	24 VDC	16 W	725 mm
591-156-002	RoLED 70/216	G	230 V	35 W	725 mm
591-156-001	RoLED 70/216	PMMA	230 VAC	35 W	725 mm
591-156-003	RoLED 70/216	G with groove	230 VAC	35 W	725 mm
591-156-004	RoLED 70/216	G	230 VAC	28 W	1030 mm
591-157-021	RoLED 70/224*	PMMA	230 VAC	33 W	1531 mm
591-157-001	RoLED 70/224	PMMA	230 VAC	33 W	1531 mm